Model V20F & V20F-24 Vertical Bandsaws

Manufactured in the United States of America

Standard Features Include:

Specifications:

Heavy Tube Steel Frame Precision Ground Cast Iron Table with replaceable throat plate **Unique Heavy Duty Roller Guides** Rotate 90 to accommodate long pieces Baldor® Motor VFD Motor Drive for variable blade speed **Magnetic Starter with** Under-voltage and **Overload protection 115 Volts at Controls** Two Speed Cast Iron Gearbox with helical gears and oil bath lubrication for guiet operation **Blade Speed Indicator** Blade Tension Indicator Flexible Arm Worklight Chip Blower (shop air) Removable Chip Tray Tiger-Tooth Bi-Metal Blade **OSHA Blade Guarding Rotary Blade Brush**

Factory Installed Options Available

Ideal Blade Welder, Grinder and Shear 24" Extended Height (Model V20-24) Miter Gauge Rip Fence, 26" 1" blade (not available on V-20-24) Spray Mist Coolant System Vacuum Nozzle Extension Tables Stock Stand 5 ft. and 10 ft. Non-Powered Roller Conveyor NFPA Electrics (w/ fused disconnect)

Consult Factory For Additional Options Specifications subject to change without notice.



2829 N. Burdick St.	* * * * * * * * * * * * * * * * * *

Kalamazoo MI 49004 Phone: 269-345-1132 Fax: 269-345-0095

www.wellsaw.com

_	*****	×*	
***	*****	**	
	* <u>*</u> * <u>*</u> *	÷1	
÷*÷	*;*;*;	*	

Capacity 20" Deep Throat 16" High Table to Guide V-20-24 24" High Blade Size 3/16" through 3/4" Std. Optional 1/2" through 1" (this option not available on V-20-24) Blade Length 14' - 9" (177") V-20-24 16 -1" (193") Band Wheels 21" Cast Aluminum with replacable rubber tires Blade Speeds Low Range 45-400 SFPM High Range 325-3000 SFPM Blade Guides Sealed Ball Bearings with 90 Rotation Feature Table Size 26" x 26" Cast Iron 5 Inside and 45 Outside Tilt Height 37-1/2" Drive Motor Three Phase 3HP 208/230/460 Volt Single Phase 2HP 115/208/230 Volt Floor Area 32"Wide x 48"Deep Height Std 83-1/2" V-20-24 91-1/2" Shipping Weight 950 lbs. Std V-20-24 1.050 lbs.

Models V20F & V20F-24 Vertical Bandsaw Now standard with VFD motor controller

20" Throat with 16" or 24" Under the Guide



Wellsaw[®]

2829 N. Burdick St. Kalamazoo, MI 49004 Phone: 269-345-1132 Fax 269-345-0095 Email: info@wellsaw.com

